

## TT230SM Printer

HellermannTyton's TT230SM thermal transfer printer is the next generation of printer available for small to medium volume users looking for an easy to use and functional thermal transfer printer. The TT230SM prints to a wide variety of materials including all of HellermannTyton labels and ShrinkTrak. The TT230SM is also Ethernet network ready, which gives the user options on placing the unit away from the host computer. The TT230SM comes with a label holder (caddy) for loading large reels behind the printer for easy dispensing and printing. There also is an optional carrying case that can be used to safely transport the printer to remote job sites.



### Product Features

- Print on ShrinkTrak
- Print on Adhesive Labels
- Print on Tiptags
- Uses standard ribbons
- Print head 300dpi
- Barcodes: standard and 2D
- Print speed up to 3" (76.2mm) per second
- Max print width 4.1" (106mm)
- Max label width 4.37 (111mm)
- Max print length 39" (101cm)
- 8MB DRAM, 2MB Flash
- Interfaces: RS232-C, Ethernet, USB v.2.0 and Centronics
- Windows drivers: 2000, XP, NT4.0, Vista, 7
- Dimensions: 7.95"(201mm) x 10.16" (258mm) x 6.81"(172mm)
- Weight 4.4lbs (2kg)

Article No.	Part No.	Type	Description	Pkg. Qty.
556-00230	<b>556-00230</b>	TT230SM	TT230SM Printer	1
556-00231	<b>556-00231</b>	CASE230SM	Carrying Case for TT230SM Printer	1
556-00236	<b>556-00236</b>	TT230BATTERY	TT230SM Rechargeable Battery Pack	1

## TT230SM Thermal Transfer Ribbons

Product Selection				Label Material										Width (W)	Length (L)
Article No.	Part No.	Type	Color	Paper	100	250	795	822	822C	900	1500	DTH	ShrinkTrak	In. (mm)	Ft. (M)
556-00147**	<b>TT822OUTSM2</b>	TT822OUTSM2	Red	•	•	•	•				•			4.33 (110)	242 (74)
556-00148**	<b>TT822OUTSM3</b>	TT822OUTSM3	Orange	•	•	•	•	•	•		•			4.33 (110)	242 (74)
556-00149**	<b>TT822OUTSM4</b>	TT822OUTSM4	Yellow	•	•	•	•	•	•		•			4.33 (110)	242 (74)
556-00150**	<b>TT822OUTSM5</b>	TT822OUTSM5	Green	•	•	•	•	•	•		•			4.33 (110)	242 (74)
556-00151**	<b>TT822OUTSM6</b>	TT822OUTSM6	Blue	•	•	•	•	•	•		•			4.33 (110)	242 (74)
556-00152**	<b>TT822OUTSM7</b>	TT822OUTSM7	Purple	•	•	•	•	•	•		•			4.33 (110)	242 (74)
556-00153**	<b>TT822OUTSM8</b>	TT822OUTSM8	Silver Gray								•		•	4.33 (110)	242 (74)
556-00143**	<b>TTDTHOUTSM</b>	TTDTHOUTSM	Black									• (5)	• (5)	4.33 (110)	242 (74)
556-00145	<b>TT822OUTSM</b>	TT822OUTSM	Black	•	(1)	•	• (1,2)	• (1,2)	•		•		• (4)	4.33 (110)	242 (74)
556-00163	<b>TTHSTOUTSM</b>	TTHSTOUTSM	Black		° (1)	°							• (4)	4.33 (110)	242 (74)
556-00169	<b>TT100OUTSM</b>	TT100OUTSM	Black	•	° (1)	°							• (4)	4.33 (110)	242 (74)
556-00190	<b>556-00190</b>	TTWHITEOUTSM	White								•			4.33 (110)	229 (70)

Use **Part No.** for ordering and **Type** for specification purposes.

• =Recommended ribbon

° =Acceptable ribbon alternative

(1) UL Recognized material / ribbon combination with HellermannTyton thermal transfer printers

(2) CSA Normal Use approved material / ribbon combination with HellermannTyton thermal transfer printers

(3) CSA Heavy Duty Use approved material / ribbon combination with HellermannTyton thermal transfer printers

(4) Meets ASM-DTL-23053/5 Class I & III, SAE-AS81531 for print performance

(5) Outstanding chemical, abrasion and solvent resistance where UL and CSA requirements are not needed

\*\* 24 ribbon minimum order

\* for use on black ShrinkTrak